## Configurer un player zebrix en adressage IP fixe

Prérequis : Clavier et souris

## Etape 1 : entrer dans la configuration

- Allumer le player
- Connecter un clavier et une souris USB sur le player zebrix
- Appuyer sur la touche "F1" pour entrer dans la "zebrix box configuration".

Zebrix box configuration – x
ID: 1c697aa37b69 Version: 20.11-03
🕟 zebrix
Network Display & Audio Touch Web admin
Network Settings (F2)
Network Diagnostic (CTRL+D)
Zebrix Server: screenv2.zebrix.net
Protocol: O http O https
No proxy server
O Proxy Address: ?
Proxy bypass list: ?
Europe: support@zebrix.net   +33 3 20 41 59 69 America: support@zebrix.us   +1 917-789-1179



si votre clavier comprend une touche "FN" (en bas à gauche), il est possible que vous deviez faire "FN" + "F1"

Last update: 2022/04/27 07:49 fr:configuration\_ip\_fixe\_nuc https://documentation.zebrix.net/doku.php?id=fr:configuration\_ip\_fixe\_nuc&rev=1651038590

## **Etape 2 : entrer dans la paramètres réseaux**

Appuyer sur la touche "F2" pour accéder aux paramètres réseaux.

zebrix box configuration	- ×
ID: 1c697aa37b69 Version: 2	20.11-03
🕟 zebrix	
Network Display & Audio Touch Web admin	
Network Settings (F2)	
Network Diagnostic (CTRL+D)	
Zebrix Server: screenv2.zebrix.net	
Protocol: http	
No proxy server	
O Proxy Address:	?
Proxy bypass list:	2
Europe: support@zebrix.net   +33 3 20 41 59 69 America: support@zebrix.us   +1 917-789-1179	

## Etape 3 : paramétrage réseau

Une fois dans les paramètres réseaux :

• sélectionner "Wired Connection 1" (ou Wireless si connecté en wifi) puis "éditer"



• Aller dans l'onglet "IPV4 Setting"

	auz. IA Secondy Deb Provy Presence of
Device:	1C:69:7A:A3:7B:69
Cloned MAC address:	
MTU:	automatic - + by
Wake on LAN:	Default Phy Unicast Multicast Ignore Broadcast Arp Magic
Wake on LAN password:	
Link negotiation:	Ignore
Speed:	100 Mb/s
Duplex	Full

Mettre "Method" en "Manual" puis cliquer sur "Add"

Last update: 2022/04/27 07:49 fr:configuration\_ip\_fixe\_nuc https://documentation.zebrix.net/doku.php?id=fr:configuration\_ip\_fixe\_nuc&rev=1651038590

		Ealting wire			A DESCRIPTION OF TAXABLE PARTY.
nnection n	ame: Wired	connection 1			
General	Ethernet	802.1X Security	DCB Proxy	IPv4 Settings	IPv6 Setting
Nethoo <mark>1</mark>	Automatic (DF	HCP) -> Passage ei	n "Manuel"		
Additiona	l static addres	sses			
Addres	\$\$	Netmask	Gateway	2	Add
					Delete
					Delete
					Delete
Addition	nal DN5 servers	5:			Delete
Addition	hal DNS servers	s:			Delete
Addition Addition DHCP c	hal DNS servers hal search dom lient ID:	s:			Delete
Addition Addition DHCP cl	hal DNS servers hal search dom fient ID: quire IPv4 addro	s:	ion to complete		Delete
Addition Addition DHCP cl	hal DNS servers hal search dom lient ID: quire IPv4 addro	s:	ion to complete		Delete
Addition Addition DHCP cl	hal DNS servers hal search dom lient ID: quire IPv4 addre	s:	ion to complete		Delete Routes
Addition Addition DHCP cl	hal DNS servers hal search dom fient ID: quire IPv4 addre	s:	ion to complete		Delete Routes

- Entrer le paramétrage IP fixe, le DNS si besoin
- Cliquer sur le bouton "Save"

		Editing Win	ed connection 1		•
nnection	name: Wired	d connection 1			
General	Ethernet	802.1X Security	DCB Proxy	IPv4 Settings	IPv6 Settings
Method:	Automatic (D	HCP)			-
Addition	al static addre	esses			
Addre	iss.	Netmask	Gateway		Add
					Delete
Additio Additio DHCP ( Re	nal DNS server nal search don client ID: quire IPv4 add	rs:	tion to complete		Routes
Additio Additio DHCP (	nal DNS server nal search don client ID: quire IPv4 add	rs:	tion to complete	(	Routes

